

トラス中空リベット

材質：鉄・アルミ・銅・黄銅・ステンレス・その他
軸径：1.2mm~6mm



単位:mm

| 寸法記号 | 呼び径 | 1.2 | 1.6 | 2.0 | 2.3 | 2.5 | 2.6 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 6.0 |
|-------|------|----------------|------|----------------|------|----------------|------------|----------------|-----|------------|----------------|------------|-----|
| d | 基準寸法 | 1.2 | 1.6 | 2.0 | 2.3 | 2.5 | 2.6 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 6.0 |
| | 許容差 | +0.02 -0.05 | | +0.02 -0.06 | | +0.02 -0.08 | | +0.02 -0.10 | | | +0.02 -0.12 | | |
| D | 基準寸法 | 2.7 | 3.6 | 4.5 | 5.0 | 5.6 | 5.7 | 6.6 | 7.7 | 8.8 | 10 | 11 | 13 |
| | 許容差 | +0 -0.3 | | | | | +0 -0.4 | | | +0 -0.5 | | +0 -0.6 | |
| H | 基準寸法 | 0.5 | 0.7 | 1.0 | 1.1 | 1.3 | 1.3 | 1.4 | 1.6 | 1.8 | 2.1 | 2.4 | 2.8 |
| | 許容差 | ±0.1 | | | | | ±0.15 | | | | | ±0.2 | |
| A | 基準寸法 | 0.8 | 1.1 | 1.3 | 1.6 | 1.7 | 1.8 | 2.1 | 2.5 | 2.8 | 3.2 | 3.5 | 4.2 |
| | 許容差 | ±0.04 | | ±0.05 | | ±0.07 | | ±0.1 | | | | ±0.12 | |
| B | 基準寸法 | 1.1 | 1.4 | 1.8 | 2.1 | 2.3 | 2.3 | 2.7 | 3.2 | 3.6 | 4.1 | 4.5 | 5.4 |
| | 許容差 | ±0.1 | | ±0.15 | | | ±0.2 | | | ±0.25 | | ±0.3 | |
| r | 最大 | 0.06 | 0.08 | 0.1 | | 0.2 | | 0.3 | | | 0.4 | | |
| a1-a2 | 最大 | 0.1 | 0.2 | | | | | 0.3 | | | 0.4 | | |
| b1-b2 | 最大 | 0.1 | | | 0.15 | | | | 0.2 | | | 0.3 | |
| C | 最大 | 0.2 | | | 0.3 | | | 0.4 | | | | 0.5 | |

?寸法

単位:mm

| 呼び径 | 1.2 | 1.6 | 2.0 | 2.3 | 2.5 | 2.6 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 6.0 |
|-----|-----------|-------|-----|-------|-----|-----|-----|-------|-----|-----|-----|-----|
| d1 | 1.3 | 1.7 | 2.1 | | 3.2 | | 3.2 | | 4.2 | | 5.3 | 6.3 |
| k | 0.7 | 1 | 1.2 | | 1.5 | | 1.8 | | 2.4 | | 3 | 3.6 |
| 許容差 | 4以下 | ±0.1 | | ±0.15 | | | | - | | | | |
| | 4を超え10以下 | ±0.15 | | ±0.2 | | | | ±0.25 | | | | |
| | 10を超え20以下 | ±0.2 | | ±0.25 | | | | ±0.3 | | | | |
| | 20を超え40以下 | - | | ±0.3 | | | | ±0.4 | | | | |
| | 40を超えるもの | - | | - | | | | ±0.5 | | | | |

寸法記号について

| | | | | | |
|---|-------|---|-------|---|----|
| d | 軸径 | A | 穴径 | ? | 長さ |
| D | 頭部直径 | B | 穴の深さ | | |
| H | 頭部の高さ | r | 首下の丸み | | |

