

# 皿リベット

材質：鉄・アルミ・銅・黄銅・ステンレス・その他  
軸径：0.6mm～6mm



単位:mm

寸法記号	呼び径	1	1.2	1.4	1.6	1.7	2	2.3	2.5	2.6	3	3.5	4	4.5	5
	基準寸法	1	1.2	1.4	1.6	1.7	2	2.3	2.5	2.6	3	3.5	4	4.5	5
d	許容差	+0.04 -0.02	+0.05 -0.02	+0.06 -0.02	+0.07 -0.02	+0.08 -0.02	+0.09 -0.02	+0.1 -0.03	+0.12 -0.03	+0.14 -0.04	+0.16 -0.04	+0.18 -0.05	+0.2 -0.05		
	基準寸法	2	2.4	2.8	3.2	3.4	4	4.6	5.0	5.2	6	7	8	9	10
dk	許容差	±0.3 0		±0.4 0				±0.5 0			±0.6 0				
	約	0.5	0.6	0.7	0.8	0.9	1	1.2	1.3	1.3	1.5	1.8	2	2.3	2.5
θ		90 <sup>+2°</sup> <sub>0</sub>													
A-B	最大	0.1		0.2								0.3			
E	最大	2°													
d1	参考	1.1	1.3	1.5	1.7	1.8	2.1	2.4	2.7	2.8	3.2	3.7	4.2	4.7	5.3


## 許容差

単位:mm

呼び径	1	1.2	1.4	1.6	1.7	2	2.3	2.5	2.6	3	3.5	4	4.5	5	6
許容差	4以下					+0.3 0				+0.4 0			-		
	4を超え10以下					+0.4 0				+0.5 0			+0.7 0		
	10を超え20以下					+0.6 0				+0.6 0			+0.8 0		
	20を超え40以下					+0.8 0				+0.8 0			+1.0 0		
	40を超えるもの					-				+1.0 0			+1.0 0		

## 寸法記号について

d	軸径	θ	皿の角度	?	長さ
dk	頭部直径	E	座面の傾き		
K	頭部の高さ	d1	穴の径		



頭部の片寄り



座面の傾き

